

Varian, Inc.
Vacuum Technologies

New Varian
Turbo Pumping Systems:
TPS-mobile / TPS-bench



Inspiring Excellence



VARIAN

The New Varian TPS-mobile and TPS-bench

Integrated Turbo Pumping Solutions!

Varian Turbo Pumping Systems provide all features required by customers:

- Completely dry, high capacity pumping systems
- Higher compression ratio and pumping speed
- Roll around Cart or Bench solutions
- Two voltages 110 / 230 V
- Versatile and Reliable
- Fast Start Up
- Turbomolecular Pumps from 46 to 600 l/sec
- T-Plus Navigator Software allows communication with your PC
- Dry Scroll or Rotary Vane Primary Pumps
- Gauges and Accessories available
- Custom solutions available



NEW!



Dry Scroll Pumps

- No maintenance required, simple tip seal replacement
- CE, UL/CUL, CSA and Semi S2-0200 certified
- Isolation valve integrated/included

NEW IDP-3

- The smallest scroll pump on the market
- Peak Pumping Speed 3.0 m³/h
- Ultimate Pressure 3.3x10⁻¹ mbar

SH-110

- Peak Pumping Speed 5.4 m³/h
- Ultimate Pressure to 6.6x10⁻² mbar

TRISCROLL 300 AND 600

- Pumping Speed up to 30 m³/h (TS600)
- Ultimate Pressure up to 9.3 x 10⁻³ mbar



Rotary Vane Pumps

- New design
- Wide Pumping speed range from 1.8 to 20.5 m³/h
- Dual Stage
- Forced Oil Circulation
- Gas Ballast Valve
- Anti-suckback valve and vent device



Turbo Molecular Pumps

- Wide Pumping speed range from 46 to 600 l/sec
- High tech-design
- High Speed and Compression
- Maximum performance at minimum costs

Technical Specifications



Benefits

- Fast, clean, dry pump down from atmosphere to 10 E^{-10} mbar
- Pressure monitor
- Portable and compact
- No maintenance required
- Low cost of ownership



Applications

- UHV System pump down
- Ion pump roughing
- Lamp and tube processing
- Cryopump regeneration
- High Vacuum Systems operation
- High and Ultra High Vacuum systems bake out

TURBOMOLECULAR PUMPS

Turbo Pump Model	Inlet Flange
TURBO-V 81-M PUMP	ISO 63, KF 40, CFF 4 1/2
TURBO-V301 NAVIGATOR PUMP	ISO 100, CFF 6"
TURBO-V551 NAVIGATOR PUMP	ISO 160, CFF 8"

PRIMARY PUMPS

Dry Scroll Pumps	Peak Pumping Speed 50Hz
IDP-3	3.0 m ³ /h
Single Phase Motor Scroll Pump SH110	90 l/min - 5.4 m ³ /h - 3.3 cfm
TriScroll 300, single phase, with Vacuum Pump Isolation Valve (VPI) 220VAC	210 l/min - 12.6 m ³ /h - 7.4 cfm
TriScroll 600, single phase, with Vacuum Pump Isolation Valve (VPI) 220VAC	420 l/min - 25.2 m ³ /h - 14.8 cfm

Rotary Vane Dual Stage Pumps	Pumping Speed 50Hz
DS 42 - 1 phase worldwide motor	1.8 m ³ /h
DS 102 - 1 phase worldwide motor	5.0 m ³ /h
DS 302 - 1 phase worldwide motor	11.6 m ³ /h
DS 402 - 1 phase worldwide motor	17.4 m ³ /h

TURBOMOLECULAR PUMPS – Pumping Speed l/sec

	Turbo-V 81M		Turbo-V 301 Nav		Turbo-V 551 Nav	
	DN 40	DN 63	DN 100	DN 160	DN 100	DN 160
Nitrogen	50	77	250	280	350	550
Helium	56	65	220	230	450	600
Hydrogen	46	50	200	210	450	510

RECOMMENDED FOREPUMPS

	TV-81M	TV-301	TV-551
Primary Pumps Dry	SH110	SH110	TS 300
Primary Pumps Mechanical	DS 42 - DS 102	DS 102	DS 302

Base Pressure with Recommended Forepump – Acc. to standard DIN 28 428

	TV-81M	TV-301	TV-551
Primary Pumps Dry	5×10^{-10} mbar (3.8×10^{-10} Torr)	$< 5 \times 10^{-9}$ mbar ($< 3.75 \times 10^{-9}$ Torr)	$< 1 \times 10^{-10}$ mbar ($< 1 \times 10^{-10}$ Torr)
Primary Pumps Mechanical	5×10^{-10} mbar (3.8×10^{-10} Torr)	$< 5 \times 10^{-10}$ mbar ($< 3.75 \times 10^{-10}$ Torr)	$< 1 \times 10^{-10}$ mbar ($< 1 \times 10^{-10}$ Torr)

TPS-bench: 5 possible standard configurations

TMP	DS42	DS102	SH110
TV81M	●	●	●
TV301		●	●

TPS-mobile: 14 possible standard configurations

TMP	DS42	DS102	DS302	DS402	IDP3	SH110	TS300	TS600
TV81M	●	●			●	●		
TV301		●	●	●	●	●	●	
TV551			●	●			●	●

MANAGING GAUGES

GUAGE KIT	In-let Flange	DIY Eyesys Mini-IMG KIT (1×10^{-3} torr to 2×10^{-9} torr)	DIY Full Range Gauge KIT (atmosphere to 3.8×10^{-9} torr)
TV81M	KF 40	9699185	9699190
	ISO 63	9699186	9699192
	CFF 4"1/2	9699187	9699193
TV301	ISO 100	9699188	9699194
	CFF 6"	9699197	9699201


For other gauge configurations, please contact your local Varian representative

CABLES

Power cords are included free of charge in all TPS-bench and TPS-mobile models, with US, EU or UK plug.

The New Varian TPS-mobile and TPS-bench

OUTLINE DRAWINGS



All specifications are subject to change without notice. Copyright by Varian SpA

Varian, Inc. Vacuum Technologies

United States and Canada

Varian, Inc
121 Hartwell Avenue
Lexington, MA 02421, USA
Tel.: +1 781 861 7200
Toll-Free: +1 800 882 7426
Fax: +1 781 860 5437
vtl.customer.service@varianinc.com

Benelux

Varian Vacuum Technologies
Herculesweg 8
4338 PL Middelburg, The Netherlands
Tel.: +31 118 671570
Fax: +31 118 671569
ed.bakker@varianinc.com
terry.wilson@varianinc.com

China

Varian Technologies China, Ltd.
Room 1648, Central Tower South
Wing
Beijing Junefield Plaza
No. 10 XuanWuMenWai Street
Beijing 100052, P. R. China
Tel.: +86 (10) 6310 8550
Toll-Free: 800 820 6556
Fax: +86 (10) 6310 0141
vtc.technical.support@varianinc.com

France

Varian s.a.
7 avenue des Tropiques
Z.A. de Courtaboeuf - B.P. 12
91941 Les Ulis cedex, France
Tel.: +33 (0) 1 69 86 38 84
Fax: +33 (0) 1 69 86 29 88
fr.vacuum.sales@varianinc.com

Germany and Austria

Varian Deutschland GmbH
Alsfelder Strasse 6, Postfach 11 14 35
64289 Darmstadt, Germany
Tel.: +49 (0) 6151 703 353
Fax: +49 (0) 6151 703 302
de.vacuum.sales@varianinc.com

India

Varian India Pvt. Ltd.
205-A, "A" wing of Galleria,
2nd floor, Hiranandani Gardens,
Powai, Mumbai-400 076, India
Tel.: +91 22-2570 8595 / 8597
Fax: +91 22- 2570 8599

Italy

Varian, Inc. - via F.lli Varian 54
10040 Leini, (Torino), Italy
Tel.: +39 011 997 9111
Toll-Free: 00 800 234 234 00
Fax: +39 011 997 9350
vtc.customer.service@varianinc.com
it.vacuum.sales@varianinc.com

Japan

Varian Technologies Japan, Ltd.
Sumitomo Shibaura Building, 8th Floor
4-16-36 Shibaura Minato-ku
Tokyo 108, Japan
Tel.: +81 3 5232 1253
Toll-Free: 0120 655 040
Fax: +81 3 5232 1710
jp.vvt.sales@varianinc.com

Korea

Varian Technologies Korea, Ltd.
Shinsa 2nd B. 2F - 966-5 Daechi-dong
Kangnam-gu, Seoul, Korea 135-280
Tel.: +82 2 3452 2452
Toll-Free: 080 222 2452
Fax: +82 2 3452 2451
vtc.technical.support@varianinc.com

Mexico

Varian, S. de R.L. de C.V.
Concepcion Beistegui No 109
Col Del Valle, C.P. 03100, Mexico, D.F.
Tel.: +52 5 523 9465
Fax: +52 5 523 9472
mariano.amezcua@varianinc.com

South East Asia

Varian Vacuum Technologies South
East Asia (SEA) - Alex Ho
H/P.: +601 2213 1253
Fax: +603 6733 8121
alex.ho@varianinc.com

Singapore

Varian Vacuum Technologies
Singapore
Unit 10-04 Helios
Biopolis @ one-north
11 Biopolis Way, 138667 Singapore
H/P.: +65 92364988
Fax: +65 64789603
william.koh@varianinc.com

Taiwan

Varian Technologies Asia, Ltd.
14F-6, No. 77, Hsin Tai Wu Road,
Sec. 1
Hsi chih, Taipei Hsien, Taiwan, R.O.C.
Tel.: +886 2 2698 9555
Toll Free: 0800 051 342
Fax: +886 2 2698 9678

UK and Ireland

Varian Ltd.
6 Mead Road, Oxford Industrial Park
Yarnton, Oxford OX5 1QU, UK
Tel.: +44 (0) 1865 291570
Fax: +44 (0) 1865 291571
uk.vacuum.sales@varianinc.com



www.varianinc.com/vacuum

